

SPECIFICATIONS

8400 series

Light Industrial Mobile Computer



		8400	8470
Communication	Options	BT Class 2 compliance	BT Class 2 compliance IEEE 802.11 b/g
	BT profile	SPP, DUN, HID	
	WLAN security	---	WEP, EAP, WPA (PSK), WPA2 (TKIP, AES, PSK)
Performance	CPU	32-bit	
	Program memory	4MB flash	
	Data memory	4MB/16MB SRAM	
	Expansion	micro SD slot with SDHC support	
	Operating power	Rechargeable lithium battery: 3.7V, 1800 mAh	
	Backup power	Rechargeable lithium battery: 3.0V, 18 mAh	
	Working hours ¹	110 hours ²	35 hours ³
	Data retention	25 days	
	Alert	Two dual-color LEDs (red/green, blue/green), vibrator, volume programmable beeper	
Data capture	Barcode scanning	Linear imager / Laser / 2D imager	
Physical characteristics	Display	160×160 display, white LED backlight	
	Keypad	29 or 39 rubber keys, white LED backlight	
	Dimension L x W x H	170.6×72.1×40.6 mm / 6.7×2.8×1.6 in.	
	Weight laser including battery	295 g / 10.4 oz.	
User environment	Operating temperature	-10° to 55°C / 14° to 131°F	
	Storage temperature	-20° to 70°C / -4° to 158°F	
	Humidity non-condensed	Storage 5% to 95% Operating 10% to 90%	
	Impact resistance	Multiple 1.5 m drops onto concrete, 5 drops on each side, 1000 tumbles at 1m, IP54	
	Electrostatic discharge	±15kV air discharge ±8kV direct discharge	
	EMC regulation	BSMI, CE, C-Tick, FCC, IC, CCC, NCC, SRMC TELEC for 8400 only	
Development support	CipherLab Power Suite BLAZE C Compiler and BASIC Compiler		
Application software	CipherLab Power Suite FORGE Application Generator including data transmission OCX, MIRROR Terminal Emulator		
Cradles	Charging and communication cradle, Ethernet cradle, GPRS cradle (EDGE/Quad-band, FCC certified)		
Accessories	4-slot battery charger, protective cover, RS232 charging and communication cable, USB charging and communication cable		
Warranty	1 year		

¹ Based on one standard laser scan per five seconds with backlight off.

² Batch mode/BT off: 110 hours / BT on is 65 hours.

³ BT off/IEEE 802.11 b/g on. The test is based on one broadcasting packet per second.

©2011 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.

ACCESSORIES



**Charging and
Communication Cradle**



Protective Cover



4-Slot Battery Charger



HEADQUARTERS
CipherLab Co., Ltd.
 12F, 333 Dunhua S. Rd., Sec. 2
 Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.cipherlab.com

CipherLab China
 J Room, 4F, No.728 West Yan'an
 Road, Changning District, Shanghai
 China 200050
Tel +86 21 3368 0288
Fax +86 21 3368 0286

CipherLab USA
 2552 Summit Avenue
 Plano, Texas USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

CipherLab Central Europe
 Willicher Damm 145
 41066 Mönchengladbach
 Germany
Tel +49 2161 56230 0
Fax +49 2161 56230 22